LPCB

This is to Certify

COMPUTIONICS LIMITED (Trading as C-TEC)

Challenge Way, Martland Park, Wigan, WN5 0LD

is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix.

EP203 Conventional three zone "class A" extinguisher control panel

which has complied with the requirements of the following:

EN 12094-1: 2003

EN 54-2: 1997 + A1: 2006 + A2: 2007 EN 54-4: 1997 + A1: 2002 + A2: 2006

Certificate No: 176c

Issue Number: 07

Date of Issue: 08 March 2013

Signed for and on behalf of LPCB

LPCB ON CERTIFICATION CONTROL OF THE CONTROL OF THE



W HUNUKUMBURE



Certificate No: 176c

COMPUTIONICS LIMITED (trading as C-TEC)

Certified Products LPCB Ref. No.

EP203 Conventional three zone "class A" extinguisher control panel 176c/01

Incorporating the following units:

SPF0000203 Main extinguisher control
SPF0000212 External relay interface
SPF0003613 Power supply unit
SPF0000214 EP214 terminator

Incorporating as modular units:

EP210S Remote Status Unit "Surface Mount" optional (See Note 1)

EP211 Economy Status Unit optional (See Note 1)

Certified with the following options with requirements from EN 12094-1:2003

4.17 Delay of extinguishing signal

4.18 Signal representing the flow of extinguishing agent

4.19 Monitoring of the status of components

4.20 Emergency hold device

4.21 Control of flooding time4.23 Manual only mode

4.26 Triggering of equipment outside the system

4.27 Emergency abort device

4.30 Activation of alarm devices with different signals

Continued....

For details of Cross-Listed products and alternative branding please see page 8.

Appendix Issue No: 07

Page: 2 of 8

Date of Issue: 08 March 2013

Signed for and on behalf of LPCB





W HUNUKUMBURE



Certificate No: 176c

COMPUTIONICS LIMITED (trading as C-TEC)

Certified Products

LPCB Ref. No.

Certified with the following options with requirements from EN 54-2:1997

7.8 Output to fire alarm device(s)

7.11 Delays to the auctioning of outputs fire alarm devices and fire routing equipment

7.13 Alarm counter

10 Test condition

Note:

- 1) Optional Remote Status Unit part No. EP210S & Economy Status Unit part No. EP211 are not certified as meeting the requirements of the standards specified.
- 2) Meets the requirements of EN12094-3:2003, Class A i.e. operational temperature range of -5°C to +40°C.

For details of Cross-Listed products and alternative branding please see page 8.

Appendix Issue No: 07

Page: 3 of 8

Date of Issue: 08 March 2013

Signed for and on behalf of LPCB





W HUNUKUMBURE



Certificate No: 176c

COMPUTIONICS LIMITED (trading as C-TEC)

Certified Products LPCB Ref. No

EP203/DE Conventional three zone "class A" extinguisher control panel

176c/01

Incorporating the following units:

German Language Variant

SPF0000203 Main extinguisher control
SPF0000212 External relay interface
SPF0003613 Power supply unit
SPF0000214 EP214 terminator

Incorporating as modular units:

EP210S Remote Status Unit "Surface Mount" optional (See Note 1)

EP211 Economy Status Unit optional (See Note 1)

Certified with the following options with requirements from EN 12094-1:2003

4.17 Delay of extinguishing signal

4.18 Signal representing the flow of extinguishing agent

4.19 Monitoring of the status of components

4.20 Emergency hold device

4.21 Control of flooding time

4.23 Manual only mode

4.26 Triggering of equipment outside the system

4.27 Emergency abort device

4.30 Activation of alarm devices with different signals

Continued....

For details of Cross-Listed products and alternative branding please see page 8.

Appendix Issue No: 07

Page: 4 of 8

Date of Issue: 08 March 2013

Signed for and on behalf of LPCB





W HUNUKUMBURE



Certificate No: 176c

COMPUTIONICS LIMITED (trading as C-TEC)

Certified Products LPCB Ref. No

Certified with the following options with requirements from EN 54-2:1997

7.8 Output to fire alarm device(s)

7.11 Delays to the auctioning of outputs fire alarm devices and fire routing equipment

7.13 Alarm counter

10 Test condition

Note:

- 1) Optional Remote Status Unit part No. EP210S & Economy Status Unit part No. EP211 are not certified meeting the requirements of the standards specified
- 2) Meets the requirements of EN12094-3:2003, Class A i.e. operational temperature range of -5°C to +40°C.

For details of Cross-Listed products and alternative branding please see page 8.

Appendix Issue No: 07

Page: 5 of 8

Date of Issue: 08 March 2013

Signed for and on behalf of LPCB





W HUNUKUMBURE



Certificate No: 176c

COMPUTIONICS LIMITED (trading as C-TEC)

Certified Products LPCB Ref. No

EP203/CON Conventional three zone "class A" extinguisher control panel under 176c/01

Context Plus Brand

Incorporating the following units:

SPF0000203 Main extinguisher control
SPF0000212 External relay interface
SPF0003613 Power supply unit
SPF0000214 EP214 terminator

Incorporating as modular units:

EP210S Remote Status Unit "Surface Mount" optional (See Note 1)

EP211 Economy Status Unit optional (See Note 1)

Certified with the following options with requirements from EN 12094-1:2003

4.17 Delay of extinguishing signal

4.18 Signal representing the flow of extinguishing agent

4.19 Monitoring of the status of components

4.20 Emergency hold device4.21 Control of flooding time

4.23 Manual only mode

4.26 Triggering of equipment outside the system

4.27 Emergency abort device

4.30 Activation of alarm devices with different signals

For details of Cross-Listed products and alternative branding please see page 8.

Appendix Issue No: 07

Page: 6 of 8

Date of Issue: 08 March 2013

Signed for and on behalf of LPCB





W HUNUKUMBURE



Certificate No: 176c

COMPUTIONICS LIMITED (trading as C-TEC)

Certified Products LPCB Ref. No

Certified with the following options with requirements from EN 54-2:1997

7.8 Output to fire alarm device(s)

7.11 Delays to the auctioning of outputs fire alarm devices and fire routing equipment

7.13 Alarm counter

10 Test condition

Note:

- 1) Optional Remote Status Unit part No. EP210S & Economy Status Unit part No. EP211 are not certified meeting the requirements of the standards specified
- 2) Meets the requirements of EN12094-3:2003, Class A i.e. operational temperature range of -5°C to +40°C

For details of Cross-Listed products and alternative branding please see page 8.

Appendix Issue No: 07

Page: 7 of 8

Date of Issue: 08 March 2013

Signed for and on behalf of LPCB





W HUNUKUMBURE



Certificate No: 176c

COMPUTIONICS LIMITED (trading as C-TEC)

ALTERNATIVE MODEL NUMBERS AND LABELLING

LPCB Ref. No.	Model No.	Alternative Model No.	Labelled	Distributors Cert/Ref No
176c/01	EP203	EP203/ORIENT	Orient Corporation Pte. Ltd.	176c-(cl-1)
176c/01	EP203	EP203/CON	Context Plus	176c-(cl-2)
176c/01	EP203	EP203/DE	C-Tec	

For details of Cross-Listed products and alternative branding please see page 8.

Appendix Issue No: 07

Page: 8 of 8

Date of Issue: 08 March 2013

Signed for and on behalf of LPCB





W HUNUKUMBURE